

NETHERLANDS - National deviations from the global regulations

FM 51-XIII TAF - civil and military stations

Both CIVIL and MILITARY STATIONS:

- 51.6.2 In case of fog, the maximum value forecast for $h_s h_s h_s$ shall be 500 ft.
In case of precipitation, the maximum value forecast for $h_s h_s h_s$ shall be 1000 ft.
- 51.10 The group (TXT_FT_F/Y_FY_FG_FG_FZ TNT_FT_F/Y_FY_FG_FG_FZ) shall not be included in the report.

CIVIL STATIONS only:

- 51.8 Change groups
If modified conditions are forecast for horizontal visibility and/or mean surface wind, the following additional criteria values shall apply:
1. Visibility
an extra criterium of 8 kilometres
 2. Wind
if the wind direction is forecast to change by 30° or more and the wind speed before and/or after the change is expected to be 10 kts or more.

STATIONS of the ROYAL AIR FORCE and the ROYAL NAVY only:

- NOTES (5) The abbreviation CNL shall not be used.
- 51.4.1 The group VVVV shall be used to forecast the lowest visibility.
- 51.6.1.5 The height of the forecast cloud layer (mass) shall be given in steps of 100 ft (30 metres) up to 5000 ft (1500 metres). Above 5000 ft steps of 1000 ft (300 metres) shall be used.
- 51.6.3 The abbreviation NSC shall not be used.
- 51.7 The code word CAVOK shall not be used.
- 51.8 Change groups
If modified conditions are forecast for horizontal visibility and/or cloud height, the associated criteria values used are derived from the 2-ATAF weather colour code.