

THE NETHERLANDS - National deviations from the global regulations

FM 51-XIV TAF - civil and military stations

Both CIVIL and MILITARY stations

- 51.6.2 In case of fog, the maximum value forecast for $h_s h_s h_s$ shall be 500 ft.
In case of precipitation, the maximum value forecast for $h_s h_s h_s$ shall be 1000 ft.
- 51.10 The group (TXT_FT_F/Y_FY_FG_FG_FZ TNT_FT_F/Y_FY_FG_FG_FZ) shall not be included in the report.

CIVIL stations only

- 51.8 Change groups
If modified conditions are forecast for horizontal visibility and/or mean surface wind, the following additional criteria values shall apply:
1. Visibility
an extra criterium of 8 kilometres
 2. Wind
if the wind direction is forecast to change by 30° or more and the wind speed before and/or after the change is expected to be 10 kts or more.

Stations of the ROYAL AIR FORCE and the ROYAL NAVY only

- NOTES (5) The abbreviation CNL shall not be used.
- 51.4.1 The group VVVV shall be used to forecast the lowest visibility.
- 51.6.3 The abbreviation NSC shall not be used.
- 51.7 The code word CAVOK shall not be used.
- 51.8 Change groups
If modified conditions are forecast for horizontal visibility and/or cloud height, the associated criteria values used are derived from the 2-ATAF weather colour code.